HSEQ PROCEDURE

HEALTH, SAFETY, ENVIRONMENTAL AND QUALITY MANAGEMENT PROCEDURE FOR WORKING AT HEIGHT

Insert Your Company Logo

TABLE OF CONTENTS

1.	AP	PROVAL	. 3
2.	PUI	RPOSE	. 4
3.	SC	OPE	. 4
4.	TER	MS AND DEFINITIONS	. 4
5.	RO	LES AND RESPONSIBILITIES	. 5
6.		OCEDURES	
	5.1.	General Height Safety	
(5.2.	Working at Height Hierarchy of Controls	
(6.3.	Working at Heights of Two Metres and Above	
(5.4.	Fall Prevention	
(5.5.	Edge Protection	9
(6.6.	Travel Restriction	9
(6.7.	Fall Arrest	9
(6.8.	Safety Harnesses	10
(5.9.	Equipment and Systems	10
(5.10.	Maintenance and Inspection	10
(3.11.	Unloading and Loading of Trucks	10
(3.12.	General Requirements for Working on Ladders	11
(5.13.	Single or Extension Ladders	11
(6.14.	Ladder Inspection and Maintenance	12
(3.15.	Stepladders	12
(6.16.	Falling Objects	13
(3.17.	Transferring Materials and Tools	13
(6.18.	Service Pits and Excavations	13
(5.19.	Scaffolding	13
(5.20.	Scaffold Inspection and Tagging	14
(3.21.	Mobile Scaffolding	15
(5.22.	Work at Heights Training	15
(5.23.	Work at Height Rescue	15
7.	REL	ATED PROCEDURES, FORMS AND DOCUMENTS	15
8.	RE\	/IEW CRITERIA	16
9.	REC	CORD MANAGEMENT	16
10	. REF	ERENCES	16
		ORK FROM HEIGHTS RESCUE FLOWCHART	

1. APPROVAL

Document Control				
Document:	HSEQ-MP-14 – Working at Height			
Version:	1.0			
Released:	sed: Insert Date			
Review Date:	+ 1 year			
Prepared By:	Insert Person	Position:	Insert	
Reviewed By:	Insert Person	Position:	Insert Posi.	
Approved By:	Insert Person	Position:	rt Posi'n	

This procedure is reviewed to ensure its continuing relevant the same same established to ensure its continuing relevant the same established to ensure its continuing relevant the same established to ensure its continuing relevant to ensure its

Amendm	Amendment Record					
Version	Date	Context	Serci	Summary of Amendments		
1.0	Insert Date	To manage risks safety associated	a	Original		
		safety associated	A A.			
		ORDER				
	•					

The latest revision of this procedure is on Insert Your Company intranet site.

It is the responsibility of the individual to ensure that any hardcopy is the current revision.

A printed version of this procedure is uncontrolled, except when provided with a document title and revision number in the field below and marked as 'Controlled Copy'.

Document Title:	Working at Height			Rev:	1.0
Uncontrolled Copy:	✓	Controlled Copy:	✓	Date:	Insert Date

© HSEQ-MP-14 Version: 1.0 Insert Date Page 3 of 18

2. PURPOSE

The purpose of this procedure is to provide guidance so that workers are not placed at risk when working at heights where there is a risk of a fall by a worker from one level to another that is reasonably likely to cause injury. This includes working with plant, ladders, scaffolding and other activities that include a risk of falling.

3. SCOPE

This procedure applies to all work conducted at height, to chable work the work to carry out the work at height safely and not experience the personnel on the ground who may be exposed to falling out.

4. TERMS AND DEFINITIONS

Term	Definition
Acceptable Level of Risk	For a risk to prope at an 'acceptable level' the active must be a so that the level of risk for the stivities. Is a sais repracticable. Is a sais repracticable. The second of risk is within acceptable safety had as asonably practicable, regard must be more to safety of injury or illness to a person, or of property down the risk; and The sable severity of the injury, illness or damage; and Whether or not the risk is avoidable by reasonable means.
	the performance of a function or exercise of a power, cludes having the qualifications, experience and competence to perform the function or exercise the power.
Аррі	 Means a ladder that meets Australian Standards as per the following list: AS 1892.1 Portable Ladders - Metal AS 1892.2 Portable Ladders - Timber AS 1892.3 Portable Ladders - Reinforced Plastic AS 1892.5 Portable Ladders - Selection, Safe Use and Care
Competent	Is a combination of attributes, including skills, training and experience, relevant to a work task or function that enables

© HSEQ-MP-14 Version: 1.0 Insert Date Page 4 of 18

Insert Your Company Logo

Term	Definition
	a person to undertake that work task safely or discharge that function in accordance with company expectations.
Permitted Work	 In relation to work involving a ladder, means work in which: The weight, size or shape of any equipment or material the person using the ladder is carrying is not likely to restrict the person's movement while the person is imbing or descending the ladder or cause the associated to lose balance on the ladder while carrying or the centre of the space between the ides of the aer for when the person is fully on the ladder of the aer for the space between the ides of the aer for the aer for the space between the ides of the aer for the aer for the ides of the aer for the aer for
Risk	The likelihood of a ne offect.
Risk Assessment	The overall kic ntiff of analysis and risk evaluation.
Suspension Trauma	Is a c min whe a p narness in a substantially uprit may exp lood pooling in the legs.
Working at Height	Mear where risk to a worker's health and afety ciated affrom one level to another that is remarkable like se injury to the person or any other cand side: • or sed workplace from which a person could all. • In any of an opening through which a person could
	In the vicinity of an edge over which a person could fall.
	n a surface through which a person could fall.
	Notwithstanding the above, any task that involves the risk of a fall equal to, or greater than two (2) metres should be treated as working at height irrespective of circumstances.
Working a. sight Hierarchy of Control	Is a process to help people choose a control that provides the highest level of safety possible in the circumstances.

5. ROLES AND RESPONSIBILITIES

Managers are responsible for:

• Ensuring that this procedure is implemented and monitored.

© HSEQ-MP-14 Version: 1.0 Insert Date Page 5 of 18